


1. Introduction

Problem

Problem: Robustly locate objects and estimate 3D 6DOF pose

- Challenges:**
- Noisy Images
 - Clutter and Occlusions
 - Inaccurate CAD Models
 - Lack of descriptive 3D features



Prior Art

3D Object Detection


Sliding Window

- Template based
- LineMOD
- Requires Depth
- Performs poorly on only depth




Descriptor Based

- On 3D Data
- PPF, SHOT, MeshHOG etc.
- Slow to compute
- Non-repeatable



Learning Based

- Random Forests (Brachmann et al)
- Designed for RGBD



Existing Framework [1]


- ✓ **PROS**
- Operates directly on point clouds (not even meshes)
 - Robust to occlusions
 - Can find multiple instances of the model
 - Reduced search space (votes for angle and model point)
 - No plane assumption is made

- ✗ **CONS**
- Can not handle low detail surfaces
 - Can not detect small objects
 - Requires ICP verification
 - Combinatorial pairing

Contributions

- We augment the entire pipeline
- No modifications to 3D feature
- Operates purely on depth images
- Cleaner Hough Space and more accurate poses
- Importance to model points
- Reduced dependency on ICP
- Integrated hypothesis verification
- Robust to large scenes with small objects

2. Method



2.1. Method Details

Hypothesis Verification


$$E_h(p, m) = D_p - \Phi(p|M, \Theta_h, K)$$

Model → Pose, Intrinsic

Depth → Projection

$$p \in \begin{cases} S_m, & \text{if } |E_h(p, m)| \leq \tau_m \rightarrow \text{On the model} \\ S_o, & \text{if } E_h(p, m) \geq \tau_o \rightarrow \text{Occlusion} \\ S_c, & \text{otherwise} \rightarrow \text{Clutter} \end{cases}$$

Score: $S_h = \left(1 - \frac{|p \in S_o|}{N_m}\right) \cdot \frac{|p \in S_m|}{N_m - |S_o|}$




Ambient Occlusion Map

$$A(p) = \frac{1}{\pi} \int_{\Omega} V(p, \omega) \vec{n} \cdot \omega \, d\omega$$

$$W(m_r, m_i) = \lambda \sqrt{A(m_r)A(m_i)}$$

Pose Averaging [4]




3. Results & Evaluation

Results on ACCV3D Dataset [2]



Table 1. Detection results on ACCV3D for different objects.

	LineMod	Drost et al.	Ours
ape	42.88%	65.54%	81.95%
cam	68.78%	84.92%	91.00%
cat	35.62%	87.30%	95.76%
driller	51.52%	81.06%	81.22%
iron	35.22%	87.06%	93.92%
Average	46.80%	81.18%	88.77%
Avg. Runtime	119ms	6.3s	2.9s

Required ICP Iterations per Method



Qualitative Results



References:

- B. Drost, M. Ulrich, N. Navab, and S. Ilic. Model globally, match locally: Efficient and robust 3d object recognition. In *Computer Vision and Pattern Recognition (CVPR), 2010 IEEE Conference on*, pages 998–1005. IEEE, 2010.
- S. Hinterstoisser, V. Lepetit, S. Ilic, S. Holzer, G. Bradski, K. Konolige, and N. Navab. Model based training, detection and pose estimation of texture-less 3d objects in heavily cluttered scenes. In *Computer Vision-ACCV 2012*, pages 548–562. Springer, 2013.
- P. F. Felzenszwalb and Huttenlocher. Efficient graphbased image segmentation. *International Journal of Computer Vision*, 59, 2004.
- F. L. Markley, Y. Cheng, J. L. Crassidis, and Y. Oshman. Averaging quaternions. *Journal of Guidance, Control, and Dynamics*, 30(4):1193–1197, 2007.