

DA Final: Symbolic 3D+t Reconstruction From Cone-Beam Projections

Jakob Vogel (Supervised by Andreas Keil)



Background

- Reconstruct the heart (coronary arteries) from cone-beam projections
- Acquisition circumstances require to consider heart beat
- State of the art approaches use (retrospective) gating and treat the filtered image sequences as quasi-static [Blondel et al., Reconstruction of Coronary Arteries, 2006], ...
- Anatomical assumptions are usually not entirely valid





Background



Courtesy of Prof. Dr. Achenbach, UK Erlangen



Background



Data provided by Dr. Lauritsch, Siemens Healthcare

Concept

- Is it possible to design an algorithm not using such assumptions?
 - Simultaneously recover shape and motion
 - Simplify reconstruction
- Symbolic reconstruction
 - Vessel segmentation yields "likelihood" or "vesselness" images
 - Dynamic reconstruction computes a "likelihood" model consisting of
 - a static spatial model and
 - deformation information
- Results can be used for tomographic reconstruction

AM

Concept



Symbolic 3D+t Reconstruction

CAMP



Vessel Segmentation

- IDP by Titus Rosu
- Multi-scale method based on [Koller et al., Multiscale Detection, 1995] and [Blondel 2006]



Shape from Silhouette

Shape from Silhouette

Shape from Silhouette

SFS reconstruction = segmentation of the reconstruction space

Level Sets

- Segmentation framework supporting extended mathematics [Sethian, Level Set Methods, 1999]
- Implicit model using a level set function

$$arPhi: egin{cases} arOmega \subset \mathbf{R}^n & o & \mathbf{R} \ oldsymbol{x} & \mapsto & arPhi(oldsymbol{x}) \ \end{pmatrix}$$

with the properties

 $\Phi(\boldsymbol{x}) \begin{cases}
 < 0 & : \ \boldsymbol{x} \text{ is inside } \Gamma \\
 = 0 & : \ \boldsymbol{x} \in \Gamma \\
 > 0 & : \ \boldsymbol{x} \text{ is outside } \Gamma
 \end{cases}$

• Signed distance constraint

Level Sets

- *Wave front approach:* The zero contour is regarded as wave front and forces are defined driving the contour towards the desired position
- Variational approach: An energy functional punishing false positives and false negatives can be used to derive a PDE [Chan et al., Active Contours without Edges, 2001]

Variational Level Sets

• Set up an energy functional depending on the level set function $E(\Phi) = \int_{\Omega} I(\mathbf{x}, \Phi(\mathbf{x}), ...) d\mathbf{x}$

• Calculate the derivative of the functional with respect to the level set function $\frac{dE}{d\Phi}(\Phi;\eta) = \int_{\Omega} I_{\Phi}(\mathbf{x},\Phi(\mathbf{x}),...) \cdot \eta(\mathbf{x}) \ d\mathbf{x}$

• An optimal segmentation over artificial time is given as solution to a PDE $\Phi_{\tau}(\mathbf{x}) = -I_{\Phi}(\mathbf{x}, \Phi(\mathbf{x}), ...) \quad \forall \mathbf{x} \in \Omega$

Level Sets

- The voxel-wise error term weights false segmentations and may contain additional regularization expressions
- Design is often using the Heaviside function

$$\mathbf{H}(x) = \begin{cases} 0 & : \ x < 0 \\ \frac{1}{2} & : \ x = 0 \\ 1 & : \ x > 0 \end{cases}$$

Error Terms

$$E_{\rm FP}(\Phi) = \sum_{i=1}^{n} \int_{\Omega_{\rm V}} \mathbf{s}_{\rm F_{P}}(\mathbf{X}) \cdot \mathbf{s}_{\rm P}(\mathbf{X}) \cdot \mathbf{p}_{\rm F_{P}}(\mathbf{X}) \, \mathrm{d}\mathbf{X}$$
$$= \sum_{i=1}^{n} \int_{\Omega_{\rm V}} \mathrm{H}\left(\frac{1}{2} - \mathrm{I}_{i}(\mathrm{P}_{i}(\mathbf{X}))\right) \cdot \left[1 - \mathrm{H}(\Phi(\mathbf{X}))\right] \cdot \left[1 - \mathrm{I}_{i}(\mathrm{P}_{i}(\mathbf{X}))\right] \, \mathrm{d}\mathbf{X}$$

Error Terms

$$E_{\rm FN}(\Phi) = \sum_{i=1}^{n} \int_{\Omega_{\rm I}} \frac{\text{false negative penalty}}{S_{\rm F_N}(\mathbf{x})} \cdot \frac{S_{\rm N}(\mathbf{x})}{S_{\rm N}(\mathbf{x})} \cdot \frac{S_{\rm F_N}(\mathbf{x})}{P_{\rm F_N}(\mathbf{x})} d\mathbf{x}$$
$$= \sum_{i=1}^{n} \int_{\Omega_{\rm I}} H\left(I_i(\mathbf{x}) - \frac{1}{2}\right) \cdot H\left(\min_{\mathbf{X}\in {\rm P}_i^{-1}(\mathbf{x})} \Phi(\mathbf{X})\right) \cdot I_i(\mathbf{x}) d\mathbf{x}$$

Remarks

- Build a composite error term
 - Different integration domains require to add weights
 - Shape regularization enforces a smooth surface

 $E(\Phi_0, \boldsymbol{\alpha}) = \lambda_{\rm FN} \cdot E_{\rm FN}(\Phi_0, \boldsymbol{\alpha}) + \lambda_{\rm FP} \cdot E_{\rm FP}(\Phi_0, \boldsymbol{\alpha}) + \lambda_{\rm shape} \cdot E_{\rm shape}(\Phi_0)$

- Differentiation yields update terms for numerical implementation
 - Voxel-wise evolution of a discrete level set function
 - Implementation of the FN updates requires a "hack"
- Separate "reinitialization" guarantees signed distance constraint

Results

Dynamic Level Sets

- A 3D+t problem could be modeled with a 4D level set function, but this approach would require extensive regularization
- Instead, the motion is modeled with a time-dependent mapping $\varphi(x, t, \alpha) = R(t, \alpha) \cdot x + T(t, \alpha) + u(x, t, \alpha)$
- A 4D level set function is then emulated using this mapping and thus implicitly regularized – as

 $\Phi(\boldsymbol{x},t,\boldsymbol{\alpha}) = \Phi_0(\boldsymbol{\varphi}(\boldsymbol{x},t,\boldsymbol{\alpha}))$

Dynamic Level Sets

- Two extensions to the static versions:
 - Every access to the level set function needs to be "deformed"
 - The deformation model needs to be updated

Dynamic Level Sets

- Evolve the motion field along with the level set function over artificial time $\frac{d\alpha}{d\tau} = -\lambda_{motion} \frac{dE}{d\alpha}$
- The derivative computes as product of several other derivatives $\frac{dE}{d\alpha} = \frac{dE}{d\Phi_0} \cdot \nabla_{\mathbf{X}} \Phi_0 \cdot \frac{d\varphi}{d\alpha}$
- Interleave the algorithms to run both optimizations *simultaneously*

Algorithm

initialize deformation to identity, shape to unknown
until convergence [artificial time]
for all discrete nodes of the reconstruction volume
for all discrete times
 reconstruct shape considering deformation
 update deformation for the current node using gradient descent
end
end

end

use models for tomographic reconstruction, diagnosis, and navigation

Experiments

- Method works for restricted motion models using phantom data
 - 100 iterations on down-sampled data take about 1 hour on a 24 core computer
 - Reconstruction volume has 50³ voxels at a 3 mm spacing

Experiments – Rigid Motion

Data Set	Noise Level	Mean	Standard Deviation	Maximum	Median
Synthetic	0%	0.54	0.30	2.19	0.47
Synthetic	25%	0.68	0.36	3.14	0.60
Synthetic	50%	2.36	2.53	11.73	1.18
Phantom	0%	0.91	0.48	4.41	0.82
Phantom	25%	0.88	0.46	4.37	0.81
Phantom	50%	4.15	2.70	9.79	3.86

$$\epsilon_{k,i} = \left\| [\widehat{\mathbf{R}}(t_i) \cdot \mathbf{X}_k + \widehat{\mathbf{T}}(t_i)] - [\mathbf{R}(\boldsymbol{\alpha}, t_i) \cdot \mathbf{X}_k + \mathbf{T}(\boldsymbol{\alpha}, t_i)] \right\|_2$$

Experiments – Deformable Motion

Data Set	Noise Level	Overlap Ratio	Sensitivity	Specificity
Synthetic	0%	85.1%	86.1%	99.9%
Synthetic	10%	84.9%	84.4%	99.9%
Synthetic	20%	84.6%	83.5%	99.9%
Synthetic	30%	83.8%	80.1%	99.9%
Synthetic	40%	83.2%	80.1%	99.9%
Synthetic	50%	81.3%	75.9%	99.9%
Phantom	0%	66.7%	75.2%	99.6%
Phantom	10%	66.6%	78.0%	99.6%
Phantom	20%	65.0%	73.8%	99.6%
Phantom	30%	67.0%	74.2%	99.6%
Phantom	40%	66.3%	72.8%	99.6%
Phantom	50%	64.7%	71.7%	99.6%

Conclusion

- Only limited sensibility to noise
- Higher resolutions, more speed, optimal motion model
- GPUs?
 - Portions could be ported right away
 - Level Set implementation requires random write access
- Tests with realistic phantom [XCAT] and real data

AWA

Thank you!

Numerical Realization

• Approximate the derivative of the level set function using a forward difference operator

$$\Phi_{\tau}(\boldsymbol{x}) pprox rac{\Phi[\tau + riangle au](\boldsymbol{x}) - \Phi[\tau](\boldsymbol{x})}{ riangle au}$$

• Use the PDE to write an update formula using artificial time steps $\Phi[au + riangle au](m{x}) pprox \Phi[au](m{x}) + riangle au \cdot \Phi_{ au}(m{x})$ $= \Phi[au](m{x}) - riangle au \cdot I_{\Phi}(\Phi(m{x}))$

Energy Term

• Shape regularization

$$E_{\text{shape}}(\Phi_0) = \int_{V_0} \delta(\Phi_0(\boldsymbol{x})) \cdot \|\nabla \Phi_0(\boldsymbol{x})\| \, \mathrm{d}\boldsymbol{x}$$

Reconstruction Errors

• Overlap ratio

$$R = \frac{2 \cdot T_p}{(T_p + F_n) + (T_p + F_p)}$$

• Sensitivity

$$S_e = \frac{T_p}{T_p + F_n}$$

• Specificity

$$S_p = \frac{T_n}{T_n + F_p}$$

• All these equations use voxel counts and depend on resolution hence